

B150001

ZH



- ▶ 主要技术特性(Main Specifications)
- ▶ 适用导线规格 (Applicable wire) : AWG32#~26#
- ▶ 适用基板厚度 (Applicable PC board thickness) : 0.6mm~1.2mm
- ▶ 温度范围 (Temperature range) : -25°C~+85°C
- ▶ 额定电压 (Voltage rating) : 250V AC, DC
- ▶ 额定电流 (Current rating) : 1A AC, DC
- ▶ 接触电阻 (Contact resistance) : $\leq 0.02 \Omega$
- ▶ 绝缘电阻 (Insulation resistance) : $\geq 500M \Omega$
- ▶ 耐压 (Withstanding voltage) : 500V AC/minute

材料及电镀规格 Material and Finish

型号 Type	材料 Material	材料厚度 Material Thickness	电镀规格 Finish
插座 WAFER	塑胶 HOUSING	PA66 UL94V-0	N/A
	针PIN	黄铜 Brass	镀锡 Tin-plated
孔座 HOUSING	PA66 UL94V-0	—	N/A
端子 TERMINAL	锡青铜 Phosphor bronze	0.15mm	镀锡 Tin-plated






产品尺寸图 Product size chart

 单位: mm 一般公差: ± 0.20

TERMINAL

B150001-4







安装尺寸(Mounting measurement)



HOUSING

B150001-2

WAFER

B150001-1
B150001-1W


HOUSING

极数 Circuits	型号 Type	尺寸(Dimensions)mm		备注型号 P. S. Type
		A	B	
2	B150001-2-02	1.5	4.5	ZH-02Y
3	B150001-2-03	3.0	6.0	ZH-03Y
4	B150001-2-04	4.5	7.5	ZH-04Y
5	B150001-2-05	6.0	9.0	ZH-05Y
6	B150001-2-06	7.5	10.5	ZH-06Y
7	B150001-2-07	9.0	12.0	ZH-07Y
8	B150001-2-08	10.5	13.5	ZH-08Y
9	B150001-2-09	12.0	15.0	ZH-09Y
10	B150001-2-10	13.5	16.5	ZH-10Y
11	B150001-2-11	15.0	18.0	ZH-11Y

B150001

ZH

WAFER

极数 Circuits	型号 Type		尺寸(Dimensions)mm		备注型号 P. S. Type	
			A	B		
2	B150001-1-02	B150001-1W-02	1.5	4.5	ZH-02A	ZH-02AW
3	B150001-1-03	B150001-1W-03	3.0	6.0	ZH-03A	ZH-03AW
4	B150001-1-04	B150001-1W-04	4.5	7.5	ZH-04A	ZH-04AW
5	B150001-1-05	B150001-1W-05	6.0	9.0	ZH-05A	ZH-05AW
6	B150001-1-06	B150001-1W-06	7.5	10.5	ZH-06A	ZH-06AW
7	B150001-1-07	B150001-1W-07	9.0	12.0	ZH-07A	ZH-07AW
8	B150001-1-08	B150001-1W-08	10.5	13.5	ZH-08A	ZH-08AW
9	B150001-1-09	B150001-1W-09	12.0	15.0	ZH-09A	ZH-09AW
10	B150001-1-10	B150001-1W-10	13.5	16.5	ZH-10A	ZH-10AW
11	B150001-1-11	B150001-1W-11	15.0	18.0	ZH-11A	ZH-11AW